

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 November 2005 (17.11.2005)


PCT

(10) International Publication Number
WO 2005/107597 A1

- (51) International Patent Classification: **A61B 6/03**
- (21) International Application Number: **PCT/JP2005/008817**
- (22) International Filing Date: **9 May 2005 (09.05.2005)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
2004-141490 **11 May 2004 (11.05.2004) JP**
- (71) Applicant (for all designated States except US): **CANON KABUSHIKI KAISHA (JP/JP); 3-30-2, Shimomaru-ku, Ohta-ku, Tokyo, 1468501 (JP).**
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **URUSHIYA, Hiroyuki (JP/JP); c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaru-ku, Ohta-ku, Tokyo, 1468501 (JP).**
- (74) Agents: **OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo, 1000005 (JP).**
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): **ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,**

[Continued on next page]

(54) Title: **RADIATION IMAGING DEVICE FOR CORRECTING BODY MOVEMENT, IMAGE PROCESSING METHOD, AND COMPUTER PROGRAM**



(57) Abstract: To high-accurately execute as much as possible correction of a body movement for reducing an artifact occurring in case of creating a tomographic image from an X-ray projected image, the coordinates of the respective corresponding points are acquired between the projected images of which the projected angles overlap each other (e.g., 0° and 360°), and the geometric transformation parameter is acquired through affine transformation or the like by using the set of the acquired coordinates. When an estimated amount of the acquired parameter is equal to or larger than a predetermined amount, the geometric transformation parameter for geometric correction is determined by using the acquired geometric transformation parameter, the geometric transformation (correction of body movement) is executed by using the determined geometric transformation parameter, and the tomographic image is created by using the corrected projected images.



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report